Dynamic Programming I

Dynamic programming is another important algorithmic technique. The main idea behind it is to solve a big problem by combining the solutions to smaller subproblems.

We usually want to maximize profit or minimize cost. A dynamic programming algorithm works by creating an array of related but simpler subproblems, and then, it computes the solution to the big complicated problem by using the solutions to the easier subproblems which are stored in this array.

We start by solving problems using dynamic programming.

Longest Monotone Subsequence Problem

Input: $d, a_1, a_2, \ldots, a_d \in \mathbb{N}$

Problem: Find L = length of the longest monotone non-decreasing subsequence.

Note: the subsequence need not be consecutive. Thus $a_{i_1}, a_{i_2}, \ldots, a_{i_k}$ is a monotone subsequence provided $1 \leq i_1 < i_2 < \ldots < i_k \leq d$ and $a_{i_1} \leq a_{i_2} \leq \ldots \leq a_{i_k}$.

Example 1 The length of the longest monotone subsequence of $\{4, 6, 5, 9, 1\}$ is 3.

We want to give a dynamic programming solution to the LMS Problem:

1 Define an array of subproblems: $R(j)$ = length of the longest monotone subsequence which ends in a_j. Then the answer would be $L = \max_{1 \leq j \leq n} R(j)$.

2 Find a recurrence: let $R(1) = 1$, and for $j > 1$,

$$R(j) = \begin{cases} 1 & \text{if } a_i > a_j \text{ for all } 1 \leq i < j \\ 1 + \max_{1 \leq i < j}\{R(i) | a_i \leq a_j\} & \text{otherwise} \end{cases}$$

3 Write an algorithm that computes R:

```
R(1) ← 1
for j : 2..d
    max ← 0
    for i : 1..j − 1
```

```
        if R(i) > max and a_i ≤ a_j then
          max ← R(i)
        end if
      end for
      R(j) ← max +1
    end for
```

and from R it is possible to compute L as was indicated in 1.

All Pairs Shortest Path Problem

Input: Directed graph $G(V, E)$, $V = \{1, 2, ..., n\}$. Cost $C(i, j) \in \mathbb{R}^+ \cup \{\infty\}$ (think of the costs as distances), $1 \leq i, j \leq n$, $C(i, j) = \infty$ if (i, j) is not an edge.

Problem: Find $D(i, j)$, the length of the shortest directed path from i to j.

Note that for a general graph on n nodes there are exponentially many (in n) paths, so exhaustive search is not feasible.

A general way of finding a Dynamic Programming solution to a problem:

1. Define a class of subproblems.
2. Give a recurrence based on solving each subproblem in terms of simpler subproblems.
3. Give an algorithm for computing the recurrence.

For our problem:

1 Define an array of subproblems: Let $A(k, i, j)$ be the length of the shortest path from i to j s.t. all *intermediate* nodes on the path are in $\{1, 2, ..., k\}$. Then $A(n, i, j) = D(i, j)$ is the solution. Notational convention: if $k = 0$ then $\{1, 2, ..., k\} = \emptyset$.

2 Define a recurrence: Initialization: for $k = 0$, $A(0, i, j) = C(i, j)$. Now for $k > 0$. To come up with a recurrence, notice that the shortest path between i and j either includes k or does not. Assume we know $A(k - 1, r, s)$ for all r, s. Suppose node k is not included. Then, obviously, $A(k, i, j) = A(k - 1, i, j)$. If node k occurs on a shortest path, then it occurs exactly once, so $A(k, i, j) = A(k - 1, i, k) + A(k - 1, k, j)$. The shortest path length is obtained by taking the minimum of these two cases:

$$A(k, i, j) = \min\{A(k - 1, i, j), A(k - 1, i, k) + A(k - 1, k, j)\}.$$

3 Write an algorithm:

It turns out that we only need space for a two-dimensional array $B(i,j) = A(k,i,j)$. To compute $A(k,*,*)$ from $A(k-1,*,*)$, we can overwrite $A(k-1,*,*)$. The following algorithm is known as *Floyd's algorithm*:

for $i : 1..n$ do
    for $j : 1..n$ do
        $B(i,j) \longleftarrow C(i,j)$ (*Initialize array B, i.e. copy C there*)
    end for
end for

for $k : 1..n$ do
(*at this point* $B(i,j) = A(k-1,i,j)$ *for all* i,j)
    for $i : 1..n$ do
        for $j : 1..n$ do
            $B(i,j) \longleftarrow \min\{B(i,j), B(i,k) + B(k,j)\}$
        end for
    end for
end for
$D \longleftarrow B$
return D

The running time of this algorithm is $O(n^3)$.

Why does it work? Worry: $B(i,k)$ or $B(k,j)$ may have already been updated, e.g. $k < j$ or $k < i$. But $B(i,k)$ and $B(k,j)$ are unchanged because the shortest path from i to k does not contain k as an intermediate node.

Simple Knapsack Problem (SKS)

Input: $d, w_1, ..., w_d, C \in \mathbb{N}$ (where C is the capacity)

Output: $\max_S\{K(S) | K(S) \leq C\}$, where $S \subseteq \{1, ..., d\}$, $K(S) = \sum_{i \in S} w_i$.

This is an NP-hard problem, which means that we cannot expect to find a polynomial time algorithm that works in general. We'll give a Dynamic Programming solution that works for relatively small C. It is important that the inputs $w_1, ..., w_d, C$ are integers (and in fact positive integers).

We will follow our standard three steps.

1 Define an array of subproblems:

Only consider first i objects $1..i$ summing up to an *intermediate* weight limit j.

$$R(i,j) = \begin{cases} True & \text{if } \exists S \subseteq \{1, ..., i\} \text{ s.t. } K(S) = j, \text{ i.e., the sum of weights is exactly } j. \\ False & \text{otherwise} \end{cases}$$

$0 \leq i \leq d$, $0 \leq j \leq C$. We can compute the solution from R as follows: $M = \max_{j \leq C}\{j | R(d,j) = True\}$.

2 Define a recurrence: Initialize: $R(0,j) = False$, $j > 0$; $R(i,0) = True$, $i = 0, 1, ..., d$.

Before writing a recurrence for $i, j \geq 1$, consider the following: Suppose we do not include object i. Then, obviously, $R(i,j) = True$ iff $R(i-1,j) = True$. Suppose object i is included. Then it must be the case that $R(i,j) = True$ iff $R(i-1, j-w_i) = True$, $j - w_i \geq 0$ (i.e., there is a subset S of objects $\{1, ..., i-1\}$ s.t. the sum of weights $K(S)$ is exactly $j - w_i$, $j \geq w_i$).

We obtain the following recurrence for $i, j \geq 1$: $R(i,j) = True$ iff $R(i-1,j) = True$ or ($j \geq w_i$ and $R(i-1, j-w_i) = True$).

3 Write an algorithm:

We will use the same space saving trick as before by using one-dimensional array $S(j)$ for $R(i,j)$.

$S(0) \longleftarrow True$ (*Initialize array for* $i = j = 0$)
for $j : 1..C$ do
    $S(j) \longleftarrow False$ (*Initialize array for* $i = 0$ *and* $j = 1..C$)
end for
for $i : 1..d$
    for decreasing $j : C$ downto 1
        if ($j \geq w_i$ and $S(j - w_i) = True$) then
            $S(j) \longleftarrow True$
        end if
    end for
    (*at this point* $S(j) = R(i,j)$ *for all* j)
end for

Note that overwriting does not create a problem here, because the values of j are considered in decreasing order $C, C-1, \ldots, 1$. Thus the array position $S(j - w_i)$ has not yet been updated when the reference is made.

Exercise: Find an input for which the program would make an error if the inner loop "for decreasing $j : C..1$" were changed to "for $j : 1..C$".

The assertion $S(j) = R(i,j)$ can be proved by induction on the number of times the inner loop body is executed. This assertion implies that upon termination of the algorithm, $S(j) = R(d,j)$ for all j. From this, the solution M can be computed as indicated above.

The time complexity of the above algorithm is $O(dC)$. Is this polynomial time (in the length of an input instance $d, w_1, \ldots, w_d, C$, where $w_i \leq C$) ? Use binary notation for the input. The length of the input is $n = O(d \log C)$. Is the time of the execution $O(dC)$ polynomial in the length of the input $O(d \log C)$? NO! For example, the binary representation of $C = 2^{100}$ has 101 bits. Thus, if we have an input of say 100 numbers of 100 bits each, then execution will take more than 2^{100} steps, which is impossibly

long. (In fact no one knows how to solve this problem feasibly for such inputs.) Notice however that this algorithm is polytime if C is written in unary notation, i.e., $\underbrace{1\ldots1}_{C}$. In this case, large values of C (such as 2^{100}) cannot be written.