NP-completeness I

Readings: Cormen et al, chapter 36.

Recommended: *Computers and Intractability*, Garey and Johnson, chapters 1-3.

Search problems: For each instance I of a search problem there is a search space $S(I)$, which can be large. We want to find some element $S \in S(I)$ satisfying a condition $C(S)$, or find $M = \max\{v(S)|S \in S(I) \text{ and } C(S)\}$ or $m = \min\{v(S)|S \in S(I) \text{ and } C(S)\}$.

SKS:

Instance: $I = \langle d, w_1, \ldots, w_d, C\rangle$, $w_i \in \mathbb{N}$, $S(I) = \{S|S \subseteq \{1, 2, \ldots, d\}\}$

Problem: Find $M = \max\{K(S)|K(S) \leq C\}$

SKS′:

Instance: Same as SKS, with the same search space $S(I)$.

Problem: Find $S_0 \subseteq \{1, 2, \ldots, d\}$ s.t. $K(S_0) = M(I)$.

Many optimization problems come in two versions:

1. Find an optimal value.
2. Find an actual structure that gives that value.

Reductions: Reduction is a fundamental notion in NP-completeness. The idea is the following: problem P_1 is reducible to problem P_2 if P_1 can be solved with the help of a P_2 solver.

Definition 1 P_1 is polytime reducible to P_2 (denoted $P_1 \xrightarrow{p} P_2$) if there is a polytime algorithm for P_1 which is allowed to access a solver for P_2. The time taken by the P_2 solver is not counted.

Example 1 JSP is the Job Selection with Profits problem. To show that SKS $\xrightarrow{p}$ JSP, we solve SKS using JSP. Namely, given an instance $\langle d, w_i, \ldots, w_d, C\rangle$ of SKS, devise an instance of JSP with the same solution as follows: $n = d$, $d_i = w_i$, $t_i = C, p_i = w_i$. Now, if we can solve JSP, then we can solve SKS.

It is important to understand the direction of reductions. In general:

$$\text{special case} \xrightarrow{p} \text{general case} \qquad \text{and} \qquad \text{easy} \xrightarrow{p} \text{hard}$$

Decision problems: A decision problem assigns either "YES" or "NO" to each instance. In general, we can associate a decision problem with a search problem. We can reduce a search problem to its associated decision problem and vice versa, so they are "equally hard".

SKD - decision problem for SKS:

Instance: $I = \langle d, w_1, \ldots, w_d, C, B\rangle$, where $B \in \mathbb{N}$ is an extra parameter denoting the lower bound for $K(S)$.

Question: Is there a subset of indices such that $B \leq K(S) \leq C$?

Claim 1 SKS $\xrightarrow{p}$ SKD

Proof of Claim. Fix an instance $I = \langle d, w_1, \ldots, w_d, C\rangle$ of SKS. We want to find $M(I)$ where $M(I) = \max\{K(S) | K(S) \leq C\}$.

Let SKD(I, B) be the answer to SKD for the instance I, B.

Idea: try $B = C$. If SKD(I, C)="YES", then $M(I) = C$. If the answer is "NO", then we can use binary search: call SKD$(I, \lceil \frac{C}{2} \rceil)$. If the answer is "YES", call SKD$(I, \lceil \frac{3C}{4} \rceil)$. If the answer is "NO", call SKD$(I, \lceil \frac{C}{4} \rceil)$. Continue reducing the size of the interval by 2 in each step, until a value B is obtained such that SKD(I, B) ="YES" and SKD$(I, B+1)$ ="NO". That B will be the solution to SKS.

The main reason to use binary search instead of linear search (trying for $B = C-1$, $B = C-2$ and so on) is that binary search is $O(\log C)$, whereas linear search is $O(C)$ and thus is not polytime when C is written in binary.

SKD$'$ decision problem for SKS$'$:

Instance: $\langle d, w_1, \ldots, w_d, C, S\rangle$, $S \subseteq \{1, 2, \ldots, d\}$.

Question: Can S be extended to an optimal solution S_0 of SKS$'$ i.e. is there a set $S_0 \subseteq \{1, 2, \ldots, d\}$ s.t. $S \subseteq S_0$ and $K(S_0) = M(I)$?

Exercise: Show SKS$' \xrightarrow{p}$ SKD$'$.

The solution to this exercise has been outlined in class; the idea is the following: first check if the set $\{1\}$ can be extended to an optimal solution. If SKD$'(I, \{1\})$ = "YES", then you keep 1 and go on to consider 2: SKD$'(I, \{1, 2\})$. If SKD$'(I, \{1\})$ = "NO", then you know that no optimal solution contains 1, so you go on to consider SKD$'(I, \{2\})$, and so on. What is the general algorithm?

Languages: We translate each decision problem into a set of strings. Σ is a finite alphabet of symbols, e.g. $\Sigma = \{0, 1, \#\}$, and Σ^* is a set of finite strings over Σ. Code I by $e(I) \in \Sigma^*$. If $m \in \mathbb{N}$, $\bar{m} \in \{0,1\}^*$ is m in binary (e.g. $\bar{6} = 110$).

For $I = \langle d, w_1, \ldots, w_d, C\rangle$, one possible encoding is $e(I) = \bar{d}\#\bar{w_1}\#\ldots\#\bar{w_d}\#\bar{C}$, $e(I) \in \{0, 1, \#\}^*$. For example $e(\langle 2, 5, 6, 3\rangle) = 10\#101\#110\#11$.

Definition 2 A language L over Σ is a subset of Σ^*. The language L_{P}, associated with a decision problem P is a set of strings $L_{\mathrm{P}} = \{x \in \Sigma^* | x \text{ codes a "YES" instance of P}\}$

in Cormen: L is "concrete decision problem".

Example 2

$$L_{\mathrm{SKD}} = \{e(\langle d, w_1, \ldots, w_d, C, B\rangle) | \langle d, w_1, \ldots, w_d, C, B\rangle \text{is a "YES" instance to SKD}\}$$

So, decision problems turn into languages.

Definition 3 A language $L \subseteq \Sigma^*$ is a *polytime language* iff there is a polytime algorithm which on input $x \in \Sigma^*$ determines whether $x \in L$. We let P denote the class of polytime languages.

Conjecture: $L_{\mathrm{SKD}} \notin P$

Note that the above definition of polytime languages is informal since we don't have a precise definition of algorithms. Thus, we need to introduce Turing Machines to formalize the notion of algorithm.

Turing machines

Recommended: Sipser, *Introduction to the Theory of Computation*, Chap 3.

Turing machines were proposed by Alan Turing in 1936.

A *Turing machine* consists of a two-way infinite tape and a finite state control. The tape is divided up into squares, each of which holds a symbol from a finite tape alphabet (usually $\{0, 1, b\}$, where b corresponds to blank).

A Turing machine M has a read/write head, that scans squares on the tape. Depending on the state of the control and the symbol scanned, it makes a move, consisting of the following: printing a symbol, shifting the head left or right one square, and assuming a new state.

Formally, a Turing machine M is specified as follows:

1. Γ (finite tape alphabet), Σ (finite input alphabet), and $\Gamma = \Sigma \cup \{b\}$ where (b is the "blank" symbol).

2. Q (finite set of states). There are 3 special states: q_0 (initial state), q_{accept} (state in which M halts and accepts), and q_{reject} (state in which M halts and rejects).

3. $\delta : (Q - \{q_{accept}, q_{reject}\} \times \Gamma) \to Q \times \Gamma \times \{L, R\}$

   $\delta(q, s) = (q', s', h)$, where q is the current state, s is the scanned symbol, q' is the new state, s' is the printed symbol and h is either L or R, corresponding to the left or right shift.

Input conventions: the input string $x \in \Sigma^*$ is written on the tape surrounded by blanks, and M starts in state q_0 scanning the leftmost symbol of x, or b if x is the empty string.

Example 3 We want to design a TM which adds 1 (in binary). Let $\Gamma = \{0, 1, b\}$, $\Sigma = \{0, 1\}$ and $Q = \{q_0, q_{\text{accept}}, q_{\text{reject}}, q_1\}$. The δ is specified by the following table:

State	Symbol	Action
q_0	0	q_0, print 0, R
q_0	1	q_0, print 1, R
q_0	b	q_1, print b, L
q_1	0	q_{accept}, print 1, L
q_1	1	q_1, print 0, L
q_1	b	q_{accept}, print 1, L

This table defines the transition function δ. Recall that $\delta(q, s) = (q', s', h)$. The first two columns are the arguments of δ, and the last column is the value of δ on those arguments. For example, from the first row we know that $\delta(q_0, 0) = (q_0, 0, \mathsf{right})$.

Definition 4 A TM M *accepts* a string x if, when we run M on input x, it eventually halts in state q_{accept}. A language accepted by M is $L(M) = \{x \in \Sigma^* | M \text{ accepts } x\}$.

Exercise: PAL = even length palindromes = $\{yy^r | y \in \{0, 1\}^*\}$, where y^r means y spelled backwards. Design a TM such that $L(M) = \text{PAL}$.